

PRODUCT DATASHEET

STARFLEX FIREHOSE



OCEAN SAFETY®

Ocean Safety,
Saxon Wharf,
Lower York Street,
Southampton,
SO14 5QF, UK.

www.oceansafety.com

Starflex Type 1 & Type 2 are high quality layflat fire hoses used by Marine & Industrial sectors around the world.

The Starflex Type 1 is an uncoated white hose approved for marine use under the Marine Equipment Directive (MED) in diameters up to 2" (52mm). Due to its lightweight design Starflex Type 1 is also ideal for general purpose firefighting, washdown and dust suppression applications. A hi-viz yellow Type 1 option is also available.

Starflex Type 2 is constructed with an all synthetic woven polyester jacket providing enhanced abrasion resistance thanks to the elastomeric coating and is available in either red or blue.

The Starflex range is manufactured to BS6391 and is suitable for use with sea water / brackish water and is immune to mildew & bacteria. Available in a choice of lengths, diameters and colours Starflex can be supplied with any British or International couplings (light alloy or gunmetal) for compatibility to existing equipment. Large stockholding ensures fast deliveries and meeting time-sensitive requirements.

KEY FEATURES

- High Quality
- Manufactured to BS6391
- MED Approved (Type 1 up to 52mm only)
- Lightweight, Flexible & Durable
- Red / Blue or White
- Choice of Lengths & Diameters
- Available with any International Couplings - Alloy & Gunmetal

Technical Specifications								
Internal Diameter	(mm)	38	45	52	64	70	75	100
	(inches)	1½	1¾	2	2½	2¾	3	4
Burst Pressure	(Bar)	45	45	45	45	45	45	36
	(PSI)	630	630	630	630	630	630	500
Working Pressure	(Bar)	15	15	15	15	15	15	12
	(PSI)	210	210	210	210	210	210	170
Coil Diameter								
30 Meters	(cm)	38	39	41	43	44	46	50
100 Feet	(inches)	15	15½	16¼	17	17½	18¼	19¾
Weight								
Uncoated	gm/M	230	240	300	350	420	530	660
Coated	gm/M	240	250	315	365	440	555	690

