

PRODUCT DATASHEET

# AUTO CLEAN AGENT (GTFE) FIRE EXTINGUISHER



**OCEAN SAFETY®**

Ocean Safety,  
Saxon Wharf,  
Lower York Street,  
Southampton,  
SO14 5QF, UK.

[www.oceansafety.com](http://www.oceansafety.com)

Ozone friendly Automatic fire Suppression Units commonly used to protect machinery/ plant and where there is a risk of fire such as in boat/vehicle engine compartments.



## KEY FEATURES

- Clean agent (Halon replacement)
- Zero ozone depletion
- 5 year warranty
- Suitable for B and C class fires
- Safe for use on electrical equipment
- Supplied with powder coated, steel wire bracket

Model	FIR0465	FIR0470	FIR0475
Capacity	1kg	1.5kg	2kg
Total Weight	2.14kg	3.10kg	3.6kg
Total Height	330mm	380mm	380mm
Total Width (Including Bracket)	95mm	125mm	125mm
Working Temp	-20 to +60 degrees	20 to +60 degrees	-20 to +60 degrees
Discharge Time	Under 10 secs at 79 degrees	Under 10 secs at 79 degrees	Under 10 secs at 79 degrees
Operating Pressure	12 bar at 20 degrees	12 bar at 20 degrees	12 bar at 20 degrees
Minimum Burst Pressure	55 bar	55 bar	55 bar
Maximum Area Pressure	1.7m <sup>3</sup>	2.5m <sup>3</sup>	3.4m <sup>3</sup>

## ORDERING INFORMATION

Part No.	Description
FIR0465	1 kg Automatic GTFE fire extinguisher
FIR0470	1.5 kg Automatic GTFE fire extinguisher
FIR0475	2 kg Automatic GTFE fire extinguisher