

OCEAN SIGNAL SAFESEA M200

The M200 can be fitted to a lifejacket and automatically activates upon inflation of the jacket

Featuring multiple methods of distress alerting, the M200 features dual infrared-white strobe lights and transmits via AIS, DSC, and 121.5 MHz to facilitate rescue efforts and thereby maximize the speed and efficiency of rescue. Compliant with the AIS Class M regulation, the M200 is a Class M DSC (Digital Selective Calling) MOB device that incorporates a durable design with a form factor that is opportunely smaller than other comparable models.

Key features

- AIS (Automatic Identification System)
- Class M Compliant (regulation ECC/DEC/(22)02)
- Integrated Tx and Rx DSC transceiver (Digital Selective Calling)*
- LEDs verify DSC distress signal receipt
- 30% (typ) smaller than competitors
- GNSS via GPS, and Galileo
- Fast accurate positioning
- 121.5 MHz Homing Signal
- IR and White Strobe Lights
- LEDs verify DSC distress signal receipt
- Automatic activation
- Simple lifejacket integration**
- 5-year battery life
- 12+ hours operational life
- 5-year warranty†
- Integrated Near Field Communication (NFC)
- Smartphone connectivity via NFC
- Ocean Signal Mobile App (IOS and Android)

† Subject to warranty statement. (Note: When used in commercial applications the warranty period is restricted to two years.)

* DSC functionality is subject to regulations of country.

** Always refer to the lifejacket manufacturer for specific instructions before installing this product directly to your lifejacket.



Code	Description
EP13190	Ocean Signal safeSEA M200